

## EX330 – Multimedia Projector

### Bold, Bright and Brilliant

The EX330 is an ultra-portable, XGA digital projector for the road warrior from Optoma. Ideal for “grab and go” presentations, the Optoma EX330 is unparalleled in size, weight and connections. It also features BrilliantColor™ technology and a DLP® chipset from Texas Instruments for crisp and amazing picture quality.

### Features

- Ultra portable 2.4lb DLP projector
- Native XGA resolution and HD compatible
- 2000 lumens and 2000:1 contrast ratio
- Connections include HDMI, VGA, s-video, composite video and USB
- Ideal presentation remote with laser pointer and page advance features
- Up to 5000 hours lamp life

### Specifications

**Display Technology**  
Single 0.55” DMD DLP Technology by Texas Instruments

**Resolution**  
Native XGA (1024 x 768)

**Maximum Resolution**  
SXGA+ (1400 x 1050)

**Brightness (Typical)**  
2000 ANSI Lumens

**Contrast Ratio**  
2000:1 (Full On/Full Off)

**Lamp Life and Type**  
3000/5000 Hours (STD/ECO)  
165W UHP

**Throw Ratio**  
1.95-2.15:1 (Distance/Width)

**Image Size (Diagonal)**  
22.9” to 302” (0.58 to 7.67m)

**Projection Distance**  
3.3’ to 39.37’ (1.0 to 12m)

**Remote Control**  
Fully Featured Remote Control w/Mouse and Laser Pointer

**Displayable Colors**  
16.7 Million

**Aspect Ratio**  
4:3 Native, 16:9 Compatible

**User Controls**  
Complete On Screen Menu Adjustments in 22 Languages

**Computer Compatibility**  
VGA, SVGA, XGA, SXGA, SXGA+, WXGA Resized, VESA, PC and Macintosh Compatible

**Video Compatibility**  
NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (576i/p, 720p, 1080i/p)

**Uniformity**  
85%

**Keystone Correction**  
± 18° Vertical

**Horizontal Scan Rate**  
15 to 100 kHz

**Vertical Refresh Rate**  
43 to 85 Hz

**Projection Lens**  
F=2.41-2.55, f=21.79~23.99mm, 1.10X Manual Zoom and Focus

**I/O Connectors**  
HDMI, VGA-In, Composite Video, S-Video, USB

**Security**  
Kensington® Lock Port

**Projection Method**  
Front, Rear, Ceiling Mount, Table Top

**Weight**  
2.4 lbs (1 kg)

**Dimensions (W x H x D)**  
8” x 2.5” x 6.1”  
(205.5 x 64 x 156 mm)



**Noise Level (STD/ECO)**  
33dB/31dB

**Power Supply**  
AC Input 100-240V, Auto-Switching

**Power Consumption**  
225 Watts (Maximum), <10 Watts (Standby)

**Operating Temperature**  
41-95° F (5-35° C) (80% Humidity), Adjustable Fan Speed for High Altitude Application

**Standard Accessories**  
AC Power Cord, VGA to VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Quick Start Guide, Warranty Card and User’s Manual

**Optional Accessories**  
Ceiling Mount, S-Video Cable, VGA to Component Cable, Composite Video Cable, DVI to HDMI Adapter, HDMI Cable, Gold Service Warranty and Panoview™ Series Screens

**Warranty**  
1 Year Limited Parts and Labor, 90 Days on Lamp

**UPC**  
796435 11 689 7

**Accessory Part Numbers**  
Lamp: BL-FP165A  
Remote: BR-5021L  
Case: BK-4022