



6.5" Coaxial Speaker, 70/100 Volt transformer, High Style Grille with Back Box, UL listed.

FEATURES

Ideal for audio and video conferencing, also used in Restaurants, Boardrooms, Class Rooms, Conference Rooms, Retail Stores, Malls, Airports, Train Stations, Warehouse and anywhere a commercial background or foreground Music or Paging is required. Designed for quick and easy Mounting makes it ideal for all ceiling type installations in new and existing constructions. Speaker system comes completely assembled.

APPLICATIONS

The QCS-CM2062T is an aggressively priced, high quality speaker/transformer/ back box package suitable for most any paging or background application including retail stores, restaurants, schools and other institutional facilities. Ships in pars and comes with c-ring and mounting channels.

Specification Technique	QCS-CM2062T
Core Speakers / Moteurs:	6.5" coax. (205mm)
Sensitivity / Sensibilité:	87dB SPL 1W/1M (average)
Max SPL:	102db RMS, 108dB Peek (70V)
Rated Power / Puissance:	60W Nominal (8 ohms), 120 W cont.
Frequency response / Bande passante:	65 HZ - 20 kHz (nominal)
Tapping 70V / Puissance en ligne:	30W,15W,7.5W,3.8W,1.9W
Impedance Tapping / Impédance :	333, 666, 1332, 2664, 5328 and 8 (ohms).
Dispersion Angle / Directivité (-6 dbA):	110 conical
Back Can:	metal
Cone:	polypropylene cone
VC Diameter:	1" (25mm) coil on Nomex former
Tweeter:	¾" (19 mm) silk dome
Transformer / Transformateurs:	30 watt max, Removable locking connector with screw-down terminals 2 input terminals. Insertion loss, less than1db. / (Perte par insertion moins que 1db)
Grill / Grille:	Aluminum
Dimensions	10.244" (260mm) Dia. & 8.629" (219mm) Deep
Mounting / Montage	8.8" (223.5mm) Bolt Circle
Net weight / Masse:	2.45 Kgs, (5.4 Lbs)
Shipping Weight:	8.85 Kgs (19.5lb)
Finish/ Couleur:	White / Blanc
Reference / Référence	QCS-CM2062T